

Heater specifications

DIMENSIONS (mm)						
	Height	Width	Depth	Weight	Flue Diameter	Capacity
SCH 140	685	550	510	130kg	151mm	140m ²
SCH 160	770	585	540	140kg	151mm	160m ²
SCH 240	800	667	566	150kg	151mm	240m ²
SCH 320	830	750	580	160kg	151mm	320m ²

CLEARANCES (mm)			HEARTH (mm)			
	Rear Wall	Side Wall	Corners	Width	Depth	Thickness
SCH 140	200	475	250	750	890	12
SCH 160	100	360	100	750	890	12
SCH 240	100	410	170	827	905	12
SCH 320	190	400	200	910	790	12

EFFICIENCY		EMISSIONS	
SCH 140	60%	1.5 (g/kg)	
SCH 160	60%	1.5 (g/kg)	
SCH 240	67%	1.7 (g/kg)	
SCH 320	66%	2.5 (g/kg)	

Authorised Distributor

LF LIVING FIRE
ESTABLISHED 1988

Richmond Showroom:
 361 Swan Street, Richmond 3121

Bayside Showroom:
 148-150 Cochrane Rd, Moorabbin 3189

03 99 777 888 www.livingfire.com.au

Firefox wood heaters are approved to Australian Standards AS/NZS 4012:2013, 1999 (Emission) and AS/NZS 2918 : 2001 (Thermal Clearance). In keeping with our policy of product innovation, Firefox Industries reserve the right to change specifications without notice. These products must be installed by a qualified person in accordance with manufacturer's instructions. Failure to do so will void the manufacturer's warranty. Overnight burn capability will depend upon installation conditions and fire wood quality. Heating capacity and burn times are a guide only as they can be affected by wet or damp wood, drafts, large glass areas, ceiling heights and lack of proper insulation etc.

SCH SERIES

**When the temperature drops...
 Nothing beats a Firefox.**



The greatest challenge for any modern wood heater is its ability to heat large open areas cleanly and efficiently.